



Straight reducing unions with taper and O-ring

Reduction

Efficient connection of fittings with
connection difference up to
3 dimensions

Safety

Both-sided sealing of the system with
O-ring as well as metallic between
taper and cone


Assembly

Easy and fast assembly with low torque,
since no deformation takes place



Straight reducing unions with taper and O-ring

Product range VKOR-..L



Type-D1/D2	Mat.-Nr.	PN	L1	L2	SW1	SW2	e	g/Stk
VKOR-12/06L	708.1074.215.21	315	34.0	33.0	22	17	3.0	56
VKOR-15/10L	708.1074.410.21	315	39.0	38.0	27	19	6.0	101
VKOR-18/10L	708.1074.575.21	315	37.5	36.0	32	19	6.0	125
VKOR-18/12L	708.1074.580.21	315	37.5	36.0	32	22	8.0	132
VKOR-22/15L	708.1074.745.21	160	43.5	42.0	36	27	10.0	215
VKOR-22/18L	708.1074.755.21	160	44.0	42.0	36	32	13.0	228
VKOR-28/18L	708.1074.870.21	160	48.0	46.0	46	32	13.0	298
VKOR-28/22L	708.1074.900.21	160	48.0	46.0	46	36	17.0	309
VKOR-35/28L	708.1074.949.21	160	51.0	48.0	50	46	22.0	415

Characteristics

- All EXMAR fittings are made of high quality stainless steel 1.4571 / AISI 316ti
- FKM O-ring as standard (other sealing on request)

EXMAR GmbH

Am Taubenbaum 6, D-61231 Bad Nauheim, Tel. +49 (0)6032 / 86986-0, Fax +49 (0)6032 / 86986-13, info@exmar.de
www.exmar.de

All data are for the purpose of providing technical information and do not constitute part of any warranty. Technical data and details subject to change. Please also refer to our general terms and conditions of sale.